

Tecnología LED

Fuentes de Alimentación 12 y 24 V - LED

24 V

Protección IP20



Ref.	Potencia máx. W	Corriente mA	Intensidad de Salida A	Max. Temperatura Carcasa °C	Dimensiones mm	Precio Pvp
186129	20 W ***	230 - 210	0.0–0.85	75	81,6x42,5x23	36,67
186624	30 W	160–140	1.25	80	103.5x36x22	16,13
186625	60 W	320–280	2.5	85	123x45x19	20,53
186626	75 W	395–345	3.125	85	180x45x19	23,47
186627	120 W	700–540	5.00	90	300x40x30	26,40

*** Formato especial extraplano

Protección IP67



Ref.	Potencia máx. W	Corriente mA	Intensidad de Salida A	Max. Temperatura Carcasa °C	Dimensiones mm	Precio Pvp
186633	30 W	385–355	0.0–3.125	80	182x42x18	23,98
186432	75 W	505–465	0.0–4.2	80	170x41x32	29,48
186433	100 W	760–700	0.0–6.25	80	180x52x30	49,23
186434	150 W	160–140	1.25	80	180x52x30	63,00
186634	200 W	1000–900	8.3	85	300x40x30	81,18

12 V

Protección IP20



Ref.	Potencia máx. W	Corriente mA	Intensidad de Salida A	Max. Temperatura Carcasa °C	Dimensiones mm	Precio Pvp
186412	6 W	70–60	0.0–0.5	75	81,6x42,5x23	8,21
186204	12 W	120	0.0–1.0	75	103.5x36x22	14,58
186620	20 W	200–190	1.68	75	123x45x19	10,27
186621	60 W	305–280	5	80	180x45x19	20,53
186622	75 W	380–350	6.25	85	180x45x19	23,47
186623	100 W	600–440	8.40	90	300x40x30	30,80

Protección IP67



Ref.	Potencia máx. W	Corriente mA	Intensidad de Salida A	Max. Temperatura Carcasa °C	Dimensiones mm	Precio Pvp
186628	30 W	160–145	2,5	80	132x42x32	24,05
186629	75 W	390–350	6,25	80	160x50x32	36,67
186630	100 W	540–480	8,34	80	207x68,5x37	58,67
186631	150 W	800–720	12,5	80	207x68,5x37	64,53